2025 Lucid Air Touring Technical Specifications

Powertrain and Charging

Drivetrain layout Dual Permanent-Magnet Electric Motors,

All-Wheel Drive

Transmission Single-speed (gear ratio 7:1)

Power (total) hp 620 Torque (total) lb-ft 885

Battery capacity kWh 92 (18 module)

Platform architecture 700V+

DC charge power Up to 250 kW

Performance

Acceleration

0 - 60 mph sec 3.4 0 - 100 km/h sec 3.6

Top Speed mph 140

Range, Consumption, and Efficiency, EPA-estimated*

	19" wheels	20" wheels	21" wheels
Range, EPA-Estimated	406 mi	377 mi	361 mi
MPGe, EPA (combined)	132	121	116
mi/kWh	4.4	4.0	3.9

^{*} Range and battery power vary with temperature, driving habits, charging and battery condition and actual results will vary.

Front Suspension	Aluminum-intensive virtual axis double wishbone. High strength steel coil springs, hollow anti roll bar.	
	Adaptive dampers with independent compression and rebound control at 500Hz (unique calibrations for driving modes).	
Rear Suspension	Aluminum-intensive multi-link. High strength steel coil springs and anti roll bar. Adaptive dampers with independent compression and rebound control at 500Hz (unique calibrations for driving modes).	
Steering Type	Electrically-assisted rack and pinion, 13.0:1 on-center ratio, 2.3 turns lock-to-lock (unique calibrations for driving modes).	
Brake Rotors and Calipers	Front: 380-mm (15-inch) Ventilated Disc, 6-Piston Fixed Rear: 375-mm (14.8-inch) Ventilated Disc, 4-Piston Fixed (rear)	
Brake System	4-wheel anti-lock braking system (ABS) with Electronic Brake Force Distribution, Traction Control, Stability Control, Torque Vectoring By Braking.	
	Electrically-assisted brake booster (hydraulically-linked, not brake-by-wire). One calibration for Smooth mode, one shared calibration for Swift/Sprint modes).	
	Accelerator pedal-actuated regenerative braking via motors.	
	User-switchable 3 mode Lucid Stability Control (changes ABS, Traction Control, Stability Control, Torque Vectoring by Braking calibrations).	
Tires		
19" wheel (standard)	Pirelli P Zero, All-Season, Lucid-specific compound and construction Front: 245/45R19 102Y M+S / Rear: 245/45R19 102Y M+S	
20" wheel (optional)	Michelin Pilot Sport, Summer, Lucid-specific compound and construction Front: 245/40ZR20 / Rear: 265/40R20	
21" wheel (optional)	Pirelli P Zero PZ4, Summer, Lucid-specific compound and construction	

Front: 245/35R21 / Rear: 265/35R21

Exterior

Wheelbase	in	116.5
Length	in	195.9
Width (with/without mirrors)	in	86.4 / 76.2
Height	in	55.4
Track (front/rear)	in	65.7 / 65.6
Ground clearance (19" wheels)	in	4.9
Turning circle, curb-to-curb	ft	39.4
Drag coefficient (19" wheels)	cd	0.197
Curb weight (19" wheels)	lbs	5,009
Interior		
Headroom – metal roof (front/rear)	in	39.6 / 37.8
Headroom – Glass Canopy roof (front/rear)	in	39.5 / 38.3
Leg room (front/rear)	in	45.4 / 37.6
Shoulder room (front/rear)	in	58.3 / 54.5
Passenger volume	cu ft	100.7
Cargo		
Cargo room - Frunk	cu ft	10.0
Cargo room - Trunk	cu ft	22.1
Total cargo volume (Frunk + Trunk)	cu ft	32.1