

Lucid Air Touring 2025 Technical Specifications – Europe

Powertrain and Charging

Drivetrain layout Dual Permanent-Magnet Electric, All-Wheel Drive

Transmission Single-speed (gear ratio 7:1)

Power (total) 462 kW (628 PS/pk/ch/hk)

Torque (total) 1,200 Nm

Battery capacity 96 kWh

Platform architecture 700+ V

AC charge power (EU) Up to 22 kW

DC charge power Up to 250 kW

Performance

Acceleration

 $0-100 \text{ km/h}^*$ s 3,6 Top speed km/h 225

Power Consumption and Range

	19" wheels	20" wheels	21" wheels
Consumption, combined (WLTP) (kWh / 100 km)	13.4	14.8	15.9 - 15.8
Range, city (WLTP) in km	937	866	807 - 813
Range, combined (WLTP) in km	794	730	677 - 682

^{*} Equipped with 21" wheels on prepared track surface.

Chassis, Suspension, and Tires

Front Suspension Aluminum-intensive virtual axis double wishbone. High strength steel

coil springs, hollow anti roll bar. Adaptive dampers with independent compression and rebound control at 500Hz (unique calibrations for

driving modes).

Rear Suspension Aluminum-intensive multi-link. High strength steel coil springs and

anti roll bar. Adaptive dampers with independent compression and rebound control at 500Hz (unique calibrations for driving modes).

Steering Type Electrically-assisted rack and pinion, 13.0:1 on-center ratio, 2,2 turns

lock-to-lock (unique calibrations for driving modes).

Brake Rotors and

Calipers

Front: 380-mm (15-inch) Ventilated Disc, 6-Piston Fixed

Rear: 375-mm (14,8-inch) Ventilated Disc, 4-Piston Fixed (rear)

Brake System 4-wheel anti-lock braking system (ABS) with Electronic Brake Force

Distribution, Traction Control, Stability Control, Torque Vectoring By

Braking.

Electrically-assisted brake booster (hydraulically-linked, not brake-by-wire). One calibration for Smooth mode, one shared calibration

for Swift/Sprint modes).

Accelerator pedal-actuated regenerative braking via motors.

User-switchable 3 mode Lucid Stability Control (changes ABS, Traction Control, Stability Control, Torque Vectoring By Braking

calibrations).

Wheels and Tires

19" wheel Front and Rear: 19 x 8

Pirelli P Zero, All-Season, Lucid-specific compound and construction

Front: 245/45R19 / Rear: 245/45R19

20" wheel Front: 20 x 8,5 / Rear 20 x 9,5

Michelin Pilot Sport, Summer, Lucid-specific compound and

construction

Front: 245/40ZR20 / Rear: 265/40ZR20

21" wheel Front: 21 x 8,5 / Rear 21 x 9,5

Pirelli P Zero, Summer, Lucid-specific compound and construction

Front: 245/35R21 / Rear: 265/35R21

Exterior

Wheelbase	mm	2.960
Length	mm	4.975
Width (with/without mirrors folded)	mm	1.936 / 2.196
Height	mm	1.409
Track (front / rear)	mm	1.663 / 1.689
Ground clearance (19" wheels / 21" wheels)	mm	126 / 136
Turning circle, curb-to-curb	m	12
Drag coefficient (19" wheels)	cd	0,197
Curb weight (19" wheels)	kg	2.262
Weight distribution (front/rear)	%	50,5 / 49,5
Interior		
-		
Headroom (front/rear)	mm	1.006 / 961
- With Glass Canopy roof	mm	1.005 / 973
Leg room (front/rear)	mm	1.154 / 954
Shoulder room (front/rear)	mm	1.481 / 1.385
Passenger volume	L	2.794,9
Cargo		
Cargo room (Frunk)	L	283
Cargo room (Trunk)	L	627
Total cargo volume	1	010
(Frunk + Trunk) (Frunk + Trunk + Rear seats	L	910 1.835
folded)	_	1.000
,		
Roof load max.	kg	75